



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



DATA SHEET

Premium Efficiency Motor: **FM1.5-18-56HC**

60 Hz

Document Generated: 31-Mar-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	1.5
RPM	1800
Phase	1
Frequency	60 Hz
Voltage	115/230
Frame Size	56HC
Enclosure	TEFC
Degree of Protection	IP54
Service Factor	1.15
Poles	4
Full Load Speed	1725
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	K
Duty Cycle	S1 / Continuous
Slip	4.17%
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Mounting Typ	C-Face with Feet
Standard	NEMA MG-1
Approvals	CSA, CE
Overload	Manual Overload

EFFICIENCY/POWER

FACTOR	LOAD EFF	P. F.
100%	79.5 %	83.1
75%	79.9 %	76.3
50%	76.6 %	64.3

TORQUE

FULL LOAD	LRT	BDT
4.49 lb.ft.	320 %	230 %

AMPERAGE INFORMATION

	115V	230V
Full Load Amps	14.5	7.3
Locked Rotor	109.7	54.8
Amps No Load	11.24	5.62

Current

BEARING INFORMATION

DE Bearing	6203 2RS
ODE	6203 2RS

Bearing

CAPACITOR INFORMATION

Start Capacitor	(1)900uF/165
Run Capacitor	V
	(1)40uF/250V

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	1045 Carbon Steel
Connection Diagram	115/230V - 6 Lead
Approximate Weight	36.5 lbs.

MOTOR DRAWING

Premium Efficiency Motor: **FM1.5-18-56HC**



Electrical Helper.org

For All Your Electric Needs Since 1928

411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL


Kelly MacMillan

Office Ph: 888-226-4917

Fax: 888-226-4917

Cell: 402-679-1579

E-Mail: kelly@electricalhelper.com



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	L	P	AB	J
E	2F1	2F2	H	BA									
2.44	3	5	0.34	2.75	6.54	6.54	12.9	3.5	0.12	8.2	7.3	5.2	1.65

SHAFT & KEY				
R	ES	S	U	NW
0.517	1.41	0.188	0.625	1.88

TERMINAL BOX				
XB	XC	XD	XE	AA
1.65	3.7	3.2	2.15	2-0.88/2-1.109

FLANGE				
AK	AJ	BF	BB	BC
4.5	5.875	3/8-16	0.16	-0.19



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



NAMEPLATE / WIRING

Premium Efficiency Motor: **FM1.5-18-56HC**

Document Generated: 31-Mar-2023
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		WorldWide Electric Corporation		SINGLE PHASE INDUSTRIAL DUTY MOTOR			
MODEL	FRAME	LOW VOLTAGE		HIGH VOLTAGE		MADE IN CHINA	
Hz	ENCL.	BLACK(P1) — LINE1	BLACK(P1) — LINE1				
HP	PH	BROWN(P2) — INS	BROWN(P2) — INS				
RPM	DUTY	ORANGE(T3) — INS	ORANGE(T3) — INS				
VOLTS	CODE	RED(T8) — INS	RED(T8) — INS				
AMPS	INS.	WHITE(T2) — LINE2	WHITE(T2) — LINE2				
S.F.	DES.	YELLOW(T4) — LINE2	YELLOW(T4) — LINE2				
SFA.	LB/WT	BLACK(T5) —	BLACK(T5) —				
MAX. AMB.	DE/ODE BRG.	ACCEPTABLE FOR FIELD WIRING ROTATION CCW-OPE TO REVERSE EITHER VOLTAGE INTERCHANGE BLACK (T5) AND RED (T8) LEADS THERMALLY PROTECTED : MANUAL					
SERIAL NO. xxxxxxxxxxxx Date Code xx/xxxx							

Model	FM1.5-18-56HC	Frame	56HC
Hz	60 Hz	Encl	TEFC
HP	1.5	PH	1
RPM	1725	DUTY	CONT
Voltage	115/230	Code	K
Amps	14.5/7.3	Ins Cl	F
S.F.	1.15	IP	IP54
SFA.	16.4/8.2	DES.	L
DE Brng	6203 2RS	WT:	36.5 lbs.
ODE Brng	6203 2RS	MAX. AMB.	40°C