



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



DATA SHEET

Premium Efficiency Motor: **PEWWE50-18-326TZ-GD,**

60 Hz

Document Generated: 11-Dec-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	50
RPM	1800
Phase	3
Frequency	60
Voltage	230/460
Frame Size	326TZ
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.25
Poles	4
Full Load Speed	1775
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	G
Duty Cycle	S1 / Continuous
Slip	1.40%
NEMA Design	B
Moment of Inertia	6.89 lb.ft.^2
Locked Rotor Time (Hot)	12 seconds
Sound Pressure Level	72 dB(A)
Number of Starts	2 Cold / 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class 1 Division 2 Groups A,B,C,D - T3C
Inverter Rating	10:1 CT / 20:1 VT
Standard	NEMA MG-1
Approvals	CSA, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	94.5	
%	0.86945%	0.82
50%	94.7 %	0.73

TORQUE

FULL LOAD	LRT	BDT
148 lb.ft.	160 %	260
%		

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	115A	57.6A
Locked Rotor Amps	725A	362.5
No Load Current	A 42A	21A

BEARING INFORMATION

DE Bearing	6312ZZ
ODE Bearing	C3 6311ZZ
	C3

ADDITIONAL DATA

F2 Suitable	Y
Shaft Material	1045 Carbon Steel
Connection Diagram	230 / 460 V - 12 Lead Δ
Lead Length	72 inches
Approximate Weight	585 lbs.



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467


AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



MOTOR DRAWING

Premium Efficiency Motor: **PEWWE50-18-326TZ-GD**



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F2	H	BA										
6.25	10.5	12	0.66	5.25	15.276	14.921	31.967	8	0.984	2.756	15.571	15.913	2.441	13.813

SHAFT & KEY				
S	ES	R	N-W	U
0.5	3.91	1.845	6.25	2.125

TERMINAL BOX				
AA	XB	XC	XD	XE
2	2.471	10.826	8.976	11.248



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



PERFORMANCE CURVES

Premium Efficiency Motor:

PEWWE50-18-326TZ-GD


Document Generated: 11-Dec-2023

Document ID:


Customer:

Motor Type	PEWWE				
Output Rating (HP)	50		FL Speed	1775	
Full Load Torque	148	lb.ft	LRT (%FLT)	160	460 volt FLA 57.6
Rotor Wk^2	6.89	lb-ft^2	BDT (%FLT)	260	230 volt FLA 115

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor: **PEWWE50-18-326TZ-GD**



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



Document Generated: 11-Dec-2023
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		NEMA Premium		3-PHASE INDUCTION MOTOR		259277			CC006A
Model				Ser No.				Low Voltage 6 4 5 7 8 9 12 10 11 1 2 3 L1 L2 L3	
HP		S.F.		IP		Encl			
Frame		P.F.		Code		Type			
Voltage	230/460	Hz		Ins Cl		Rating	°C Amb Cont		
Amps		RPM		Design		Date			
Nom.Eff.	FL	% 3/4		% 230/460 V	10:1 CT 20:1 VT PWM VFD	1.0SF			
				DE Brng					
Class I DIV. 2 Groups A B C D				Amb.40°C					
Class I Zone 2 II C				Amb.55°C					
				ODE Brng					
50Hz		HP		V		A	rpm	1.0SF	
WorldWide Electric Corporation									

Model	PEWWE50-18-326TZ-GD						
HP	50	S.F.	1.25	I	IP55	Encl	TEFC
Prame	326TZ	P.F.	0.86	Code	G	Type	BJPE
Voltage	230/460	Hz	60	Ins Cl	F	Rating	40°C
Amps	115/57.6	RPM	1775	Design	B	DE Brng	6312ZZ
C3 Nom.Eff.	94.5%	3/4 Eff	94.9%			ODE Brng	6311ZZ C3

50Hz			
HP	50	Volts	200/400
		200V	
	FLA	135A	RPM
	400V FLA	67.5	1475